

1

3

5

7

9

## DIGITAL LOCK FOR STEEL LOCKERS

Electronic locks

This new digital combination lock has been uniquely designed to fit quickly and easily to most traditional metal lockers. There are no wires to connect and no tricky pins to align. The 2 part design simply clicks together and is secured with 2 nuts.

The lock can be fitted to new lockers and also offers a quick, simple way of upgrading existing mechanical systems.

A 4 digit pin code opens and closes the lock and an 8 digit master code can be used by the site manager. A mechanical key override also ensures the locker can be opened in the event of an emergency.

The standard AA batteries will last up to 80,000 operations and the condition can be checked at any time by simply pressing a button. When they eventually need to be changed it is a simple operation with no need to remove the lock from the locker.

The lock can be supplied in day-use mode for temporary assignment or in private mode for permanent assignment. It can also be changed at any time in the future.

## Designed to fit industry standard "three-hole" footprint




4)


6


8)

0)









## **Standard Features**

- Black or silver or white finish as standard
- Mechanical emergency override key
- High quality keypad
- LED lights multi function
- Key press LED indicator
- Re-lock LED indicator
- Audible "beep" on key press (can be disabled)
- 8-digit master code
- 4-digit user codes
- Automatic timed unlock option
- Technician mode (allows access wtih master key without erasing user pin)
- · Battery level indicator
- 2 x AA batteries included
- Up to 80,000 cycles per pair of batteries
- Discrete logo (can be customized)

A: Lowe & Fletcher Inc. 650 Airport Place Norton Shores MI-49441 T: (616) 994-0490 F: (616) 994-0480 E: sales@loweandfletcherinc.com W: www.loweandfletcherinc.com



A Lowe & Fletcher Group Company

## Strong zinc alloy construction

- Sliding bolt to fit recessed, multi-point latching systems
- Simple click together fit, with 2 nuts to secure and no wires to connect

۲

00

0

JA

3 0

73.5

-ocking systems for industry

Product ID: 3790