




ELLO brings a new and fresh feel to the lockers world. The new look of latch locks is proudly introduced to the market place.


Main Features:

- 🔑 Free wheel turning system
- 🔑 Body and head made in ZAMAK
- 🔑 New design giving a fresh impetus to the latch lock world
- 🔑 Various fixing hole sizes
- 🔑 Suited for padlock loops from 5 to 8mm diameter
- 🔑 Three Body Lengths 31,70mm, 20,00mm, 19,50mm


Four Available fixings



Quick washer
(For 32 & 20mm body length)



Quick Fixing
(Only 20mm body length)
Panel thickness from 0,8 to 1,6mm




Nut
(For 32 & 20mm body length)




Screw fixing for wood panels
(Only available with 19mm body length and restrained head)

Two Available Head Shapes

Ergonomic Design = ELOH



Restrained Design = ELOW



ELOW	Latch lock with low head	
ELOH	Latch lock with high ergonomic head	
Body Lengths		
09	19,5mm – special version with 4 screws fixing – only with ELOW	
20	20MM	
32	31,7MM	
Piercing		
K	16,6 x diameter 19,1mm	
H	Diameter 17,7 x 20,3mm (only available on snap in fixing version – ELOW/H20)	
J	16,0 x diameter 19,1mm	
Z	Diameter 23mm (only available on special version with 4 screws – ELOW09)	
Shutter		
0	Shutter not available	
Cam Fixing		
C6	Cam fitted with a clip (max 2mm cam thickness)	
S6	Cam with star piercing fixed with screw and washer	
S7	Cam with cross piercing fixed with screw and washer	
Key Rotation		
01	90° Clockwise	
Finish		
7B	Body and head in Bright Nickel	
2A	Body and head in Bright Chrome	
8H	Body in Bright Nickel and head in Black	
1A	Body in Bright Nickel and head in White powder coating <small>(RAL9010)</small>	
Lock Fixing		
N	Nut Fixing	
H	Horseshoe clip (please specify panel thickness)	
S	Snap In fixing (please specify panel thickness)	
Z	Fixing with 4 screws (not supplied)	
Master		
0	No masterkey system	



EXAMPLE

ELOW	32	K	0	LC	01	7B	N	0
-------------	-----------	----------	----------	-----------	-----------	-----------	----------	----------

ELOW Lock – 32mm body length- fixing hole size diameter 19,1 x 16,6mm -- Cam fitted with e-clip - 90° Movement Clockwise – nickel finish – Nut fixing - Without Master.

Lowe & Fletcher Inc. 650
Airport Place
Norton Shores MI-49441

T: +1 (616) 994 0490
F: +1 (616) 994 0480
E: sales@loweandfletcherinc.com
W: www.loweandfletcherinc.com



L&F A Lowe & Fletcher Group Company